



LONG DISTANCE KVM EXTENSION SYSTEMS

Lindy' s cutting-edge KVM extension systems allow you to operate and maintain office servers remotely, far from the server rooms improving workflows and productivity.

To connect the transmitter and the receiver you can use either Cat.x or fibre optic cables, depending on the distance and the required performance of the signals.

We offer a broad portfolio of KVM products to ensure you find a solution that perfectly meets your needs.

Discover Lindy' s extensive KVM product range!



HDMI KVM EXTENDE

HDMI is the most widely used standard for highresolution audio and video transmission. From computers to displays, media players to TVs and projectors, HDMI is the ideal connection solution for uncompressed high frame rate 4K and 8K UHD performance. It is also an integral part of the world's first transmission standard for KVM extender systems, HDBaseT.

50m CAT.6 HDMI & USB KVM EXTENDER

3

- · Allows remote control of a PC using a keyboard, mouse and monitor at distances of up to 50m over Cat.6 cable
- · Supports resolutions up to Full HD 1080p/1920x1200
- Supports USB keyboard and mouse signals



100m C6 HDBaseT 2.0 HDMI & USB KVM EXTENDER

- Extends HDMI 2.0 compatible signals up to 100m using HDBaseT™ 2.0 Technology
- · Uses a single cable to extend HDMI, USB, RS-232, IR, Ethernet and audio signals
- Supports resolutions up to Ultra HD 4096/3840x2160p60
- Integrated Power over Cat.6 (PoC) functionality, requires only a single power supply



No. 38209

100m CAT.6 DUAL HEAD HDMI, **USB & RS-232 EXTENDER**

- Controls a high performance PC, with two displays, in a remote location with USB, Serial & bi-directional IR support
- Extends two 1920x1080@60Hz HDMI signals up to 100m using HDBaseT 2.0 over a single Cat.6 cable
- · Audio pass-through allows the connection of amplifiers, speakers and microphones



No. 39371

300m FIBRE OPTIC HDMI 18G & USB KVM EXTENDER

- Extends 4K HDMI & KVM signals up to 300m using LC fibre cable
- Supports resolutions up to 3840x2160@60Hz 4:4:4 8bit
- 2 USB Type A ports for connecting Keyboards, Mice & other USB HIDs
- · Bi-directional IR & RS-232 Pass-through



No. 39392



DISPLAYPORT KVM EXTENDERS

DisplayPort is widely used for the transmission of audio and video signals. The latest version supports resolutions up to 8K at high refresh rates and the uncompressed colour sampling ratio of 4:4:4. Modern laptops can generate DisplayPort signals via a USB Type C connector. Using adapters, this port can be converted to the standard DP connector which is commonly used in Displayport KVM Extenders.

100m CAT.6 DISPLAYPORT 1.2 & USB KVM EXTENDER

- Extends 4K DisplayPort 1.2 & USB KM signals up to 100m using standard Cat.6 network cable
- Supports resolutions up to 3840x2160@60Hz 4:4:4 8bit

7

- Bi-directional PoC (Power over Cable) functionality for power from a single power supply
- Bi-directional IR & RS-232 control



From Cat.x to Fibre Optic

Historically, AV and KVM extenders used Cat.x twisted pair cable to connect the transmitter and the receiver.

For short distance applications of less than 150m, Cat.x cable is the ideal solution. It provides easy installation for relatively low cost and supports typically required maximum resolutions.

For longer distances and higher resolution requirements, fibre optic based extension systems have become more prevalent.

With fibre optic based extension systems, it is possible to achieve transmission lengths of several kilometres.

300m FIBRE OPTIC DISPLAYPORT 1.2 & USB KVM EXTENDER

- Extends 4K DisplayPort 1.2 & USB KM signals up to 300m using LC fibre cable
- Supports resolutions up to 3840x2160@60Hz 4:4:4 8bit
- Three USB Type A ports for connecting keyboards, mice & other USB HIDs
- Automatic EDID functionality for seamless compatibility



No. 39376



Transmission

Bandwidth /

Additional Functions

Resolution

Distance



HDMI KVM EXTENDER RANGE



50m CAT.6 KVM EXTENDER

HDMI, USB & AUDIO

Up to 50m via Cat.6 cable

HDMI 4.95G resolutions

up to 1920x1080@60Hz



100m CAT.6 KVM EXTENDER HDBaseT, HDMI, DVI, DP, USB

Up to 100m via Cat.6 cable

HDMI 10.2G resolutions

USB, IR, RS-232, Ethernet,

3.5mm audio and PoC

(HDBaseT 2.0)

up to 4K60 4:2:0

No. 38209



100m CAT.6 DUAL HEAD KVM EXTENDER HDMI, USB, IR & RS232, HDBaseT

Up to 100m via Cat.6 cable

2x HDMI signals up to Full HD resolutions with only one Cat.6 cable

USB, IR, RS-232, digital & analogue audio

No. 39374

(HDBaseT 2.0)



300m FIBRE OPTIC HDMI KVM EXTENDER USB, IR & RS-232

Up to 300 m over LC / LC 0M3 50/125 duplex fibre optic cable

HDMI 18G resolutions up to 4K60 4: 4: 4

USB, IR, RS-232,

No. 39392

No. 39371

USB (HID), EDID

DISPLAYPORT KVM EXTENDER RANGE





	100m CAT.6 DP 1.2 KVM EXTENDER USB, IR & RS232	300m FIBRE OPTIC DP 1.2 KVM EXTENDER USB
Transmission Distance	Up to 100m via Cat.6 cable	Up to 300m with LC fibre optic cable
Bandwidth / Resolution	Up to 3840x2160@60Hz 4:4:4 8Bit	Up to 3840x2160@60Hz 4:4:4 8Bit
Additional Functions	2 x USB (HID), IR, RS-232 and PoC	3 x USB (HID)
	No. 39375	No. 39376