

ROLINE DesignSecure 2000

Product No.	19.40.1220
Manufacturer	ROLINE
Manufacturer No.	19.40.1220
EAN (single piece)	7611990976744



- Compact designed UPS in futuristic design
- For Workstations and PCs
- LineInteractive UPS
- AVR (Automatic Voltage Regulation)
- Digital status display
- Integrated overvoltage protection
- Telephone/Modem connections
- USB Port for advanced Power Management Software (incl, in content of delivery)
- EMI/RFI Noise Filter
- Dimensions (HxLxW) 168 x 105 x 334 mm
- Weight: 6.3 kg
- Backup Time: up to 4 Minutes

Technical specifications	
Manufacturer	ROLINE
Product group	UPS
Product type	UPS Line Interactive
Colour	black / silver
Scope of delivery	UPS, Software, Cable Set
Classification (IEC 62040-3)	VI-SS-333
UPS technology	Line Interactive

Power class	2000 ... 3000 VA
Output (VA/W)	2000 / 1200
Backup time	2 min
Backup time full/half-load	2 / 4 min
Dimensions (HxWxD)	192 x 130 x 382 mm
Mounting form	Tower
Voltage (input)	230 V
Voltage (output)	230 V
Output voltage regulation	yes
Frequency	50 Hz
Connector type (input)	cold connector IEC320 C14
Outputs	6
Connector type (output)	6 cold connector IEC320 C13
Phase in/output	230V/230V / 50Hz
Over current protection	EMI,- RFI-Filter
Max. quantity of delay expansion units	0
Delay expansion unit	--
Slots for adapter card	0
Slot for adapter card	--
Interface	USB
USB 2.0 Interface	yes
Hot swap batteries	no
Bypass	no
Additional over current protector	Telephone/Fax
Activity	Display
Activity LED	--
Activity Display	yes

incl.Management Software	Windows
Internal cooling	Passive
Ambient temperature	0-40 °C
Mains connection	Cold appliance connection
Battery category	Industrial battery
Number of batteries	2 pieces
Battery Voltage	12 V
Battery Capacity	7 Ah
Battery type	Pack
Battery	built-in
Battery technology	Lead-acid
Operating temperature min.	0 °C
Operating temperature max.	40 °C
Height	192 mm
Width	130 mm
Depth	382 mm
Weight	16 kg
Height of packaging (single piece)	320 mm
Width of packaging (single piece)	500 mm
Depth of packaging (single piece)	260 mm
Package weight (single piece)	17.916 kg
Backup Time	
Capacity (VA / W)	minutes
200/120	65
400/240	28

600/360	14
800/480	9,5
1000/600	7
1200/720	5
1400/840	4
1500/900	3,5
1600/960	3
1800/1080	2,5
2000/1200	2