# ROLINE Industrial Switch, 6x RJ-45, 2x ST, unmanaged

| | |
|---|---|
| **Product No.** | 21.13.1153 |
| **Manufacturer** | ROLINE |
| **Manufacturer No.** | 21.13.1153 |
| **EAN (single piece)** | 7611990176717 |






**Network-Switch for use in a industrial environment**

- Fast Ethernet switch with 6x 10/100Base-T ports and 2x 100Base-FX ports
- Wide operating temperature range for use in a temperature critical environment
- Support DIN rail mounting
- Industrial-rated Emission and Immunity performance
- Provides wire speed store-and-forward switching
- Supports IEEE 802.3x flow control for full-duplex operation
- Supports Back-pressure flow control for half-duplex operation
- Power: Input: 7-30V DC, Consumption: 6.5W (max.)
- Operating Temperature: - 20 °C - +70 °C
- DC Input via terminal block or DC power jack (6.3mm/2.0mm)
- As power supply we recommend using 21.13.1226

| Technical specifications | |
|---|---|
| Manufacturer | ROLINE |
| Product group | Industrial Networking |
| Product type | Network Switch |
| Colour | black |
| Scope of delivery | 1x switch, 1x terminal block, 1x product CD-ROM |
| Network standard | Fast Ethernet |

| | |
|---|---|
| LAN (Mbps) | 10/100 |
| Quantity of ports | 8 |
| Fast Ethernet Ports RJ-45 | 6 |
| Fast Ethernet Ports Fibre | 2 |
| Mounting form | DIN Rail |
| Management | no |
| Stackable | no |
| Dimensions (HxWxD) | 106 x 40 x 140 mm |
| Power supply | External power supply unit |
| Mains connection | Loose cable / screw terminals |
| Operating temperature min. | -20 °C |
| Operating temperature max. | 70 °C |
| Height | 106 mm |
| Width | 40 mm |
| Depth | 140 mm |
| Weight | 552.1 g |
| Height of packaging (single piece) | 70 mm |
| Width of packaging (single piece) | 150 mm |
| Depth of packaging (single piece) | 210 mm |
| Package weight (single piece) | 0.65 kg |