


ROLINE S/FTP PiMF Cable Cat.7 (Class F), Solid Wire, LSOH, 300 m

Product No. 21.15.0004
Manufacturer ROLINE
Manufacturer No. 21.15.0004
EAN (single piece) 7611990180073



- Cable for structured building cabling
- Impedance: 100 Ohm
- 300 meter/box
- Construction:
 - 8 lines, solid copper wire, AWG23
 - pairs shielded with aluminium foil
 - complete shielding in tinned copper braid
- Halogen-free, flame retardant, low smoke
- Colour: grey

Technical specifications	
Manufacturer	ROLINE
Product group	Twisted Pair Cable
Product type	Installation cable
Colour	grey
Length	300 m
Contents	300 m

Shield type	S/FTP (PiMF)
Transfer quality	Cat7 / Class F
Impedance	100 Ohm
Quantity of wires	8
Conductor cross section (AWG)	AWG 23
Inner conductor material	BC (Bare Copper)
Conductor type	Solid wire
Cable LSOH	yes
Material (external cable mantle)	PVC
Fire protection class	Eca
Weight	14.97 kg
Height of packaging (single piece)	240 mm
Width of packaging (single piece)	380 mm
Depth of packaging (single piece)	400 mm
Package weight (single piece)	17.39 kg