


ROLINE UTP Patch Cord Cat.5e (Class D), PoE, grey, 0.5 m

Product No.	21.15.0500
Manufacturer	ROLINE
Manufacturer No.	21.15.0500
EAN (single piece)	7611990133857



Cat.5e
Class D

U/UTP

PoE

RJ45 patch cable for network, LAN and Ethernet connections with PoE support. Flexible unshielded UTP patch cord with gold-plated RJ-45 connectors, moulded kink protection and 4-pair stranded copper wire.

Patch cable for networking connections between devices. Prepared unshielded Twisted Pair cable with RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire.

For a structured cabling system we recommend to use the following components: ROLINE Cat.5e UTP Cable, Solid Wire, AWG24: 21.15.0512 (100 m), 21.15.0511 (300 m); ROLINE Cat.5e Flush/Surface Mount Wall Jack, unshielded: 25.16.8506 (white), 25.16.8501 (ivory)/25.16.8406 (white), 25.16.8401 (ivory); ROLINE Cat.5e 19" Patch Panel, 24 Ports, unshielded: 26.11.0349 (black), 26.11.0347 (light grey); ROLINE Cat.5e UTP Patch Cord, grey, 5 m: 21.15.0505. Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class D specifications.

Technical specifications	
Manufacturer	ROLINE

Product group	Twisted Pair Cable
Product type	U/UTP patch cord
Colour	grey
Length	0.5 m
Shield type	U/UTP
Transfer quality	Cat5e / Class D
Impedance	100 Ohm
Quantity of wires	8
Conductor cross section (AWG)	AWG 26
Power over Ethernet (PoE)	yes
Inner conductor material	BC (Bare Copper)
Conductor type	Stranded
Crossed	no
Locking lever	no
Anti-kink sleeve	Moulded-on
Colour (Spout)	grey
Cable LSOH	no
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Weight	20.5 g
Height of packaging (single piece)	10 mm
Width of packaging (single piece)	160 mm

Depth of packaging (single piece)	120 mm
--------------------------------------	--------

Package weight (single piece)	0.021 kg
----------------------------------	----------