
# ROLINE S/FTP Patch Cord Cat.6 Component Level, LSOH, black, 5 m

| | |
|---|---|
| **Product No.** | 21.15.2655 |
| **Manufacturer** | ROLINE |
| **Manufacturer No.** | 21.15.2655 |
| **EAN (single piece)** | 7611990135646 |








Patch cable for networking connections between devices. Prepared double shielded Twisted Pair cable with screened RJ-45 connectors on both ends. Durable due to moulded kink protection. Flexible cable, suitable for narrow bending. High quality plugs with gold plated contacts. Contact settings 1:1, in accordance with the EIA/TIA 568 standard. Construction: 4-pair stranded copper wire. Complete braid shielding. Pairs shielded with aluminium clad polyester foil. Halogen-free, flame retardant, low smoke.

**100% Component Level testing**

| Technical specifications | |
|---|---|
| Manufacturer | ROLINE |
| Product group | Twisted Pair Cable |
| Product type | S/FTP patch cord (PiMF) |
| Colour | black |
| Length | 5 m |
| Shield type | S/FTP (PiMF) |
| Transfer quality | Cat6 / Class E |

| | |
|---|---|
| Component-Level certified | yes |
| Impedance | 100 Ohm |
| Quantity of wires | 8 |
| Conductor cross section (AWG) | AWG 26 |
| Power over Ethernet (PoE) | yes |
| Inner conductor material | BC (Bare Copper) |
| Conductor type | Stranded |
| Crossed | no |
| Locking lever | yes |
| Anti-kink sleeve | Moulded-on |
| Colour (Spout) | black |
| Cable LSOH | yes |
| Side 1 Connector Type | RJ-45 |
| Side 1 Connector Gender | Male |
| Side 2 Connector Type | RJ-45 |
| Side 2 Connector Gender | Male |
| Connector Type RJ45 | Standard |
| Weight | 183 g |
| Height of packaging (single piece) | 30 mm |
| Width of packaging (single piece) | 180 mm |
| Depth of packaging (single piece) | 200 mm |
| Package weight (single piece) | 0.216 kg |