
VALUE UTP Patch Cord Cat.6A (Class EA), blue, 5 m

Product No.	21.99.1455
Manufacturer	VALUE
Manufacturer No.	21.99.1455
EAN (single piece)	7611990120994











• The cheap solution for data transfer rates of up to 10 Gbit/s and a bandwidth of 500 MHz
• Patch cable for networking connections between devices
• Prepared shielded Twisted Pair cable (PiMF) with RJ-45 connectors on both ends.
• Durable due to moulded kink protection.
• Flexible cable, suitable for narrow bending.
• Impedance: 100 Ohm
• Contact settings 1:1, in accordance with the EIA/TIA 568 standard.
• Construction: 8 lines, pairs shielded with aluminium foil, complete shielding in tinned copper braid

For a structured shielded Cat.6a cabling system we recommend to use the following components:

VALUE Cat.6a UTP Cable, Solid Wire, 300 m: 21.99.1681
Flush Mount Wall Jack for Keystones: 25.16.8579
Surface Wall Mount Frame: 25.16.8484
VALUE Cat.6a Keystone, RJ-45, shielded: 26.99.0366
19" Keystone Patch Panel: 26.11.0358 / 26.11.0359
VALUE Cat.6a S/FTP Patch Cord, 5 m: 21.99.0875

Technical specifications

Manufacturer	VALUE
Product group	Twisted Pair Cable
Product type	U/UTP patch cord
Colour	blue
Length	5 m
Shield type	U/UTP
Transfer quality	Cat6A / Class EA
Quantity of wires	8
Conductor cross section (AWG)	AWG 24
Power over Ethernet (PoE)	yes
Inner conductor material	BC (Bare Copper)
Conductor type	Stranded
Crossed	no
Assignment	1:1
Locking lever	yes
Anti-kink sleeve	Moulded-on
Colour (Spout)	blue
Cable LSOH	no
Side 1 Connector Type	RJ-45
Side 1 Connector Gender	Male
Side 2 Connector Type	RJ-45
Side 2 Connector Gender	Male
Connector Type RJ45	Standard
Operating temperature min.	-20 °C
Operating temperature max.	60 °C

Weight	189.6 g
Height of packaging (single piece)	30 mm
Width of packaging (single piece)	140 mm
Depth of packaging (single piece)	210 mm
Package weight (single piece)	0.188 kg