

ROLINE Cat.5e (Class D) 19" Patch Panel, 24 Ports, UTP, grey

Product No.	26.11.0347
Manufacturer	ROLINE
Manufacturer No.	26.11.0347
EAN (single piece)	7611990159727



- The UTP patch panels are compliant with EIA/TIA 568 TSB40a
- LSA-plus technology
- 24 ports
- Colour: Light grey

For a structured unshielded cabling system we recommend to use the following components:

- ROLINE Cat.5e UTP Cable, Solid Wire, AWG24: 21.15.0512 (100 m), 21.15.0511 (300 m)
- ROLINE Cat.5e Flush/Surface Mount Wall Jack, unshielded: 25.16.8506 (white), 25.16.8501 (ivory)/25.16.8406 (white), 25.16.8401 (ivory)
- ROLINE Cat.5e 19" Patch Panel, 24 Ports, unshielded: 26.11.0349 (black), 26.11.0347 (light grey)
- ROLINE Cat.5e UTP Patch Cord, grey, 5 m: 21.15.0505

Our in-house laboratory has tested this cable-plug combination, in a Channel of 100 meters, in compliance with Class D specifications.

Technical specifications	
Manufacturer	ROLINE
Product group	Connection technology TP
Product type	Patchpanel Cat.5e
Colour	grey

Shield type	Not screened
Transfer quality	Cat5e / Class D
Cabinet system	19"-Technique
Quantity of ports	24
Assembly cable connection	Krone LSAplus
Assignment	EIA/TIA 568A & 568B
Modular assembly	no
Shield contacts	No
Connection direction	Straight
Height units	1 U
Height	43.5 mm
Width	482.6 mm
Depth	48.3 mm
Weight	485.2 g
Height of packaging (single piece)	70 mm
Width of packaging (single piece)	100 mm
Depth of packaging (single piece)	490 mm
Package weight (single piece)	1 kg