


DATASHEET

Power Cable CEE7/7 90° - C13 180° Black 1,0 m, 3 x 0.75 mm²



General data

The power cable Protective Contact 90° - C13 180° from EFB-Elektronik is designed as a black power cable with earthed plug (type F) and IEC socket. The combination of right-angle plug and straight socket supports space-saving power connections in European applications.

- Black finish with robust PVC sheath
- Three-pin cable with protective conductor for power supply
- 1.0 m length for compact connection paths

The polyvinyl chloride (PVC) sheath material, the nominal voltage of 250 V and the nominal current of 10 A characterize the cable as a practical solution for typical mains connections. The design with protective conductor and the country-specific suitability for Europe complement the connection concept for use on standardised devices.

Technical details

- Brand: EFB-Elektronik
- Core Count: 3
- Connector 1: Safety plug (type F), right-angled
- Connector 1 angle: 90°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Outer jacket colour: black
- Country suitability: Europe
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Rated current: 10 A
- Protective conductor available

This datasheet was created automatically on 27-09-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180° Black 1,0 m, 3 x 0.75 mm²

Technical properties	
Cable printing	VDE H05VV-F 3G0.75mm ² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Plug with protective contact (type F), right-angled
Connection 2	Cold device plug straight, female
Connector 1 angulation	90 °
Connector 2 angulation	180 °
Country suitability	Europe
Halogen free	False
Locking mechanism	False
Material outer sheath	PVC
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	JT008 VDE 250V 16A
Protective conductor	True
Security certificates	VDE
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants								
ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	Nominal cross section conductor	Outer diameter approx.
EK504.0,5V2	Power Cable CEE7/7 90° - C13 180° Black 0.5 m, 3 x 0.75 mm ²	black	IP20	0.5 m	10 A	250 V	0.75 mm ²	6.5 mm
EK504.0,75V2	Power Cable CEE7/7 90° - C13 180° Black 0.75 m, 3 x 0.75 mm ²	black	IP20	0.75 m	10 A	250 V	0.75 mm ²	6.5 mm
EK504.1V2	Power Cable CEE7/7 90° - C13 180° Black 1,0 m, 3 x 0.75 mm ²	black	IP20	1.0 m	10 A	250 V	0.75 mm ²	6.5 mm

This datasheet was created automatically on 27-09-2026 . Technical changes reserved.



DATASHEET

Power Cable CEE7/7 90° - C13 180° Black 1,0 m, 3 x 0.75 mm²

EK504.2V2	Power Cable CEE7/7 90° - C13 180°, Black 2.0 m, 3 x 0.75 mm ²	black	IP20	2.0 m	10 A	250 V	0.75 mm ²	6.5 mm
EK504.3V2	Power Cable CEE7/7 90° - C13 180°, Black 3.0 m, 3 x 1.00 mm ²	black	IP20	3.0 m	10 A	250 V	1.0 mm ²	7.0 mm
EK504.5V2	Power Cable CEE7/7 90° - C13 180°, Black 5.0 m, 3 x 1.00 mm ²	black	IP20	5.0 m	10 A	250 V	1.0 mm ²	7.0 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 27-09-2026 . Technical changes reserved.

