DATASHEET

Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm²



General data

The C20 180° to C19 180° IEC extension from EFB-Elektronik is designed for standard-compliant power connections in Europe and the UK. With a black outer jacket and a length of 5.0 m, it is suitable for applications where a reliable and at the same time practical extension of IEC connections is required.

- IEC extension with IEC plug and IEC socket straight
- 180° angulation design on both connectors for compact cable routing
- Black outer jacket with a length of 5.0 m for flexible applications

The structure with 3 cores, protective conductor and sheath material made of polyvinyl chloride (PVC) supports a robust cable design for technical installations. With a nominal voltage of 250 V, the IEC extension is designed for the intended area of application and, with its suitability for Europe and the UK, fits into different system environments.

Technical details
- Brand: EFB-Elektronik
- Connector 1: IEC plug
- Connector 1 angle: 180°
- Connection 2: IEC socket straight
- Connector 2 angle: 180°
- Core Count: 3
- Outer jacket colour: black
- Sheath material: Polyvinyl chloride (PVC)
- Nominal voltage: 250 V
- Protective conductor available
- Country suitability: Europe & UK

Technical properties

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm²

Cable printing	VDE H05VV-F 3G1.5mm² ZHEJIANG JINTING NUCLEAR CABLE CO.,LTD. www.efb-elektronik.de CE
Colour outer sheath	black
Connection 1	Cold device plug (IEC 60320)
Connection 2	Cold device plug straight, female
Connector 1 angulation	180 °
Connector 2 angulation	180 °
Country suitability	Europe&UK
Halogen free	False
Locking mechanism	False
Material outer sheath	PVC
Nominal voltage	250 V
Number of cores	3
Oil resistant (acc. EN 60811-2-1)	False
Oil resistant (according to EN 60811-404)	False
Plug imprint	ST6D ENEC 250V 16A
Protective conductor	True
Security certificates	VDE,ENEC
Spiralized cable	False
Type of packaging	Labeled polybag
Warranty	24 month
With cord switch	False

Available variants

ArtNr.	Bezeichnung	Colour outer sheath	Degree of protection	Length	Nominal current	Nominal voltage	Nominal cross section conductor	Outer diameter approx.
EK519.1	Extension Cable C20 180° - C19 180°, Black, 1.0 m, 3 x 1.50 mm²	black	IP20	1.0 m	16 A	250 V	1.5 mm²	8.6 mm
EK519.1,8	Extension Cable C20 180° - C19 180°, Black, 1.8 m, 3 x 1.50 mm²	black	IP20	1.8 m	16 A	250 V	1.5 mm²	8.6 mm
EK519.2,5	Extension Cable C20 180° - C19 180°, Black, 2.5 m, 3 x 1.50 mm²	black	IP20	2.5 m	16 A	250 V	1.5 mm²	8.6 mm

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm²

EK519.5	Extension Cable C20 180° - C19 180°, Black, 5.0 m, 3 x 1.50 mm²	black	IP20	5.0 m	250 V	1.5 mm²	8.6 mm

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION