

DATASHEET

USB2.0 Extension Cable B-B, M-F (panel type), 1.0m, black, Classic



Classic



General data

Supports data transmission rates up to 480 Mbit/s. Wire construction: AWG28 / AWG24. Shielded: folie + braiding. Plug moulded.

Technical properties

3D	False
ARC	False
Backwards compatible	True
Bandwith	480 Mbit/s
Bending radius (dynamic/static)	45 mm
CEC	False
Cable set	False
Chip	False
Compliant with	Scanner, Printer, External hard drive, Medical equipment
Connection type connection 1	Stecker
Connection type connection 2	plug
Connector 1 angulation	180°

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

USB2.0 Extension Cable B-B, M-F (panel type), 1.0m, black, Classic

Connector 2 angulation	180°
Contact Plating	gold-plated
Crush resistance (short/long)	1 kg/cm ²
DSC	False
Dust cover	No
HDMI Power	False
HDMI certified	False
HEC (Ethernet channel)	False
Halogenfree	No
Kink protection	False
MSA	False
MST	False
Material Connector Housing	PVC molded
Material Inner Conductor	TC
Material jacket	PVC
Max. mating cycles	1500
Model	Adapter
Number of poles connection 1	4
Number of poles connection 2	4
Number of shieldings	double
Operating temperature	-10 - 80 °C
PCIe Data transfer	False
Plug dimensions Side 1	36.5mm x 8mm x 6.6mm
Plug dimensions Side 2	21.6mm x 8mm x 7.26mm
Printing	HI-SPEED USB Revision 2.0 SHIELDED 28AWG/1PR+24AWG/2C VW-1 80°C 30V
Scope of delivery	1 x USB Cable
Shielded	True
Speed	480 Mbit/s
Temperature	-10 - 80 °C
Tensile strength (short/long)	98,1 N
Type of connector connection 1	USB-B
Type of connector connection 2	USB-B
Type of packaging	plastic bag
Type of signal	Digital
VESA certified	False

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.



DATASHEET

USB2.0 Extension Cable B-B, M-F (panel type), 1.0m, black, Classic

VRR	False
Various lengths cable set	2 x 1m
Version	USB 2.0 High-Speed
Warranty	24 months
With termination resistor	False
eARC	False

Available variants

ArtNr.	Bezeichnung	Colour	Length		
K5293SW.0,5V2	USB2.0 Extension Cable B-B, M-F (panel type), 0.5m, black, Classic	Black	0.5 m		
K5293SW.1,8V2	USB2.0 Extension Cable B-B, M-F (panel type), 1.8m, black, Classic	Black	1.8 m	4.5 mm	24+28AWG
K5293SW.1V2	USB2.0 Extension Cable B-B, M-F (panel type), 1.0m, black, Classic	Black	1.0 m	4.5 mm	24+28AWG
K5293SW.3V2	USB2.0 Extension Cable B-B, M-F (panel type), 3.0m, black, Classic	Black	3.0 m	4.5 mm	24+28AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 26-09-2026 . Technical changes reserved.

