DATASHEET

SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 15,0m, black





General data

This black SVGA extension cable from EFB-Elektronik is a versatile solution for extending VGA connections. It supports video resolutions of up to 1920 × 1200 and is particularly suitable for use with laptops and monitors. With a bandwidth of 12 Mbit/s, it enables the reliable transmission of various media signals.

- Extension cable: male to female connector, ideal for bridging longer distances
- Nickel-plated contacts for stable signal transmission
- Maximum data transfer rate: 12 Mbit/s

Product Description
The cable is protected by a durable PVC outer jacket. Both the VGA DBHD15 male connector and the VGA DBHD15 female connector feature an SPCC connector housing, helping to prevent damage and ensure long-term reliability.

Technical Specifications
- Connector 1: VGA DBHD15 male (15-pin)
- Connector 2: VGA DBHD15 female (15-pin)
- Connector angle: 180° (straight)
- Signal type: Analogue
- Cable diameter: 7.5 mm
- Jacket material: PVC
- Maximum mating cycles: 500

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 15,0m, black

• Brand: EFB-Elektronik

Package Contents
• 1 × VGA extension cable

Technical properties	
3D	False
ARC	False
Backwards compatible	True
Bandwith	12 Mbit/s
Bending radius (dynamic/static)	25,4 mm
CEC	False
Cable set	False
Cable type (passive/active/optical)	passive
Chip	False
Color depth	8-Bit
Compliant with	Laptop,Gaming Monitor,Monitor,Webcams
Connection type connection 1	Stecker
Connection type connection 2	Jack
Connector 1 angulation	180°
Connector 2 angulation	180°
Contact Plating	nickel-plated
DSC	False
Dust cover	No
HDMI Power	False
HDMI certified	False
HEC (Ethernet channel)	False
Halogenfree	No
Kink protection	False
MSA	False
MST	False
Material Connector Housing	SPCC
Material Inner Conductor	BC
Material jacket	PVC
Max. mating cycles	500
Model	Adapter
Number of poles connection 1	15

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION

DATASHEET

SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 15,0m, black

Number of poles connection 2	15
Number of shieldings	triple
Operating temperature	-5 – 45 °C
PCIe Data transfer	False
Plug dimensions Side 1	34.0 x 15.8 x 45.7mm
Plug dimensions Side 2	34.0 x 15.8 x 45.7mm
Printing	STYLE 2919 80°C 30V VW-1 VGA Cable
Scope of delivery	1 x VGA Cable
Shielded	True
Speed	12 Mbit/S
Supported video standards	1920x1200
Temperature	-20 – 60 °C
Tensile strength (short/long)	39,2 N
Type of connector connection 1	VGA DBHD15
Type of connector connection 2	VGA DBHD15
Type of packaging	plastic bag
Type of signal	Analog
VESA certified	False
VRR	False
Warranty	12 months
With termination resistor	False
eARC	False

Available variants

ArtNr.	Bezeichnung	Colour	Length	Diameter	AWG
K5327SW.1,8V2	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 1.8m, black	Black	1.8 m	7.5 mm	28AWG
K5327SW.15V2	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 15,0m, black	Black	15.0 m	7.5 mm	28AWG
K5327SW.5V2	SVGA/HDTV Extension Cable, 2x HD-DSub 15, M-F, 5,0m, black	Black	5.0 m	7.5 mm	28AWG

Note on Intended Use

This data sheet is intended solely to describe the technical characteristics of the product. It does not replace an assessment of the product's suitability for a specific application. The user is responsible for ensuring that the product is used in accordance with its technical specifications and applicable legal and regulatory requirements.

This datasheet was created automatically on 25-09-2026 . Technical changes reserved.

EFB-Elektronik GmbH
Striegauer Straße 1
33719 Bielefeld

fon: +49 521 40 41 8-0
fax: +49 521 40 41 8-50

info@efb-elektronik.de
www.efb-elektronik.de

WIR SORGEN FÜR VERBINDUNG
WE CARE FOR CONNECTION