

Part No. 36304

5M DISPLAYPORT CABLE 1.2, CROMO LINE





DESCRIPTION

Superior performance and design DisplayPort cable
Supports UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit
Chrome design ABS housing, 24K gold plated connectors and contacts
Triple shielded cable, corrosion resistant, high performance tinned copper 28AWG conductors
DisplayPort 1.2, 4K, 3D, 21.6Gbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Cromo Line DisplayPort cables are high performance, designer connections that combine premium construction materials with striking connector architecture.

Cromo Line DisplayPort Cables feature triple shielded construction with 28AWG conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit, including stereoscopic 3D, are supported. Cromo Line DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

Cromo Line cables feature sleek chrome design ABS housing to complement the aesthetics of style focused commercial and home applications.

Cromo Line DisplayPort cables are available in lengths from 0.5m to 5m.

RELATED PRODUCTS

36300 - 0.5m (1.64ft) 36301 - 1m (3.28ft) 36302 - 2m (6.56ft) 36303 - 3m (9.84ft)

36304 - 5m (16.40ft)

CONNECTION D

5M DISPLAYPORT CABLE 1.2, CROMO LINE

CONNECTORS

Connector A

Connector B

DisplayPort Male

DisplayPort Male

Chrome plated ABS

Connector Plating

Pin Construction

Phosphor Bronze

Pin Plating

Dimensions (approx.) WxDxH

DisplayPort Male

DisplayPort Male

ABS

24K Gold 3µm

Phosphor Bronze

24K Gold 15µm

19.7x38.9x12mm

[0.77x1.53x0.47in]

CABLE CONSTRUCTION

Length5m (16.40ft)StandardDisplayPort 1.2

Colour Grey
Type Round

Jacket Diameter 7.3mm (0.29in)

Jacket Material PVC

Conductor Material Tinned Copper

Conductor Gauge 28AWG

Shielding Copper Braid 85%

SPECIFICATONS

Supported Bandwidth 21.6Gbps

Maximum Resolution 4096x2160@60Hz 4:4:4 10bit

Nominal Attenuation 300kHz-825MHz <5dB

825MHz-2.475GHz <5dB 2.475GHz-4.125GHz <12dB 4.125GHz-5.1GHz <20dB

Minimum Bend Radius 73mm (2.87in)

 Operating Temperature
 $-20^{\circ}\text{C} - 80^{\circ}\text{C} (-4^{\circ}\text{F} - 176^{\circ}\text{F})$

 Storage Temperature
 $-25^{\circ}\text{C} - 85^{\circ}\text{C} (-13^{\circ}\text{F} - 185^{\circ}\text{F})$

ATC Approved -

MISCELLANEOUS

Packaging Type Polybag Warranty (Years) 10

Certificated RoHS, REACH, UL

PURCHASING INFORMATION

No. 36304

EAN 4002888363044

AVAILABLE IN OTHER LENGTHS

36300 - 0.5m (1.64ft) 36301 - 1m (3.28ft) 36302 - 2m (6.56ft) 36303 - 3m (9.84ft) 36304 - 5m (16.40ft)