

Part No. **36307**

## 2M CROMO MINI DISPLAYPORT CABLE

**MINI DP MALE TO MALE**

### DESCRIPTION

Superior performance and design Mini DisplayPort cable  
Supports UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit  
Chrome design ABS housing, 24K gold plated connectors and contacts  
Triple shielded cable, corrosion resistant, high performance tinned copper 32AWG conductors  
DisplayPort 1.2, 4K, 3D, 21.6Gbps; 10 year warranty

CROMO Mini DisplayPort Cables feature triple shielded construction with 32AWG conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit, including stereoscopic 3D, are supported. CROMO Mini DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

CROMO cables feature sleek chrome design ABS housing to complement the aesthetics of style focused commercial and home applications.

### RELATED PRODUCTS

36305 - 0.5m (1.64ft)

36306 - 1m (3.28ft)

36307 - 2m (6.56ft)

## 2M CROMO MINI DISPLAYPORT CABLE

### CONNECTORS

<b>Connector A</b>	Mini DisplayPort Male
<b>Connector B</b>	Mini DisplayPort Male
<b>Housing Material</b>	Chromed plated ABS
<b>Connector Plating</b>	24K Gold 3µm
<b>Pin Construction</b>	Phosphor Bronze
<b>Pin Plating</b>	24K Gold 15µm
<b>Dimensions (approx.) WxDxH</b>	10x32x7mm (0.39x1.26x0.28in)

### SPECIFICATONS

<b>Supported Bandwidth</b>	21.6Gbps
<b>Maximum Resolution</b>	4096x2160@60Hz 4:4:4 10bit
<b>Nominal Attenuation</b>	300kHz-825MHz <5dB 825MHz-2.475GHz <5dB 2.475GHz-4.125GHz <12dB 4.125GHz-5.1GHz <20dB
<b>Minimum Bend Radius</b>	55mm (2.17in)
<b>Operating Temperature</b>	-20°C - 80°C (-4°F - 176°F)
<b>Storage Temperature</b>	-25°C - 85°C (-13°F - 185°F)
<b>ATC Approved</b>	-

### PURCHASING INFORMATION

<b>No.</b>	36307
<b>EAN</b>	4002888363075

### CABLE CONSTRUCTION

<b>Length</b>	2m (6.56ft)
<b>Standard</b>	DisplayPort 1.2
<b>Colour</b>	Grey
<b>Type</b>	Round
<b>Jacket Diameter</b>	5.5mm (0.22in)
<b>Jacket Material</b>	PVC
<b>Conductor Material</b>	Tinned Copper
<b>Conductor Gauge</b>	32AWG
<b>Shielding</b>	Copper Braid 85%

### MISCELLANEOUS

<b>Packaging Type</b>	Polybag
<b>Warranty (Years)</b>	10
<b>Certificated</b>	RoHS, REACH, UL

### AVAILABLE IN OTHER LENGTHS

36305 - 0.5m (1.64ft)
36306 - 1m (3.28ft)
36307 - 2m (6.56ft)