

Part No. **36314**

5M CROMO MINI DISPLAYPORT TO DISPLAYPORT CABLE

MINI DP MALE TO DP MALE**DESCRIPTION**

Superior performance and design Mini DisplayPort to DisplayPort cable
Supports UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit
Chrome design ABS housing, 24K gold plated connectors and contacts
Triple shielded cable, corrosion resistant, high performance tinned copper 32AWG conductors
DisplayPort 1.2, 4K, 3D, 21.6Gbps; 10 year warranty

CROMO Mini DisplayPort To DisplayPort Cables feature triple shielded construction with 32AWG conductors for premium performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@60Hz 4:4:4 10bit, including stereoscopic 3D, are supported. CROMO DisplayPort cables are capable of delivering 4:4:4 colour spacing for the most accurate colour representation possible.

CROMO cables feature sleek chrome design ABS housing to complement the aesthetics of style focused commercial and home applications.

RELATED PRODUCTS

36313 - 3m (9.84ft)
36314 - 5m (16.40ft)

5M CROMO MINI DISPLAYPORT TO DISPLAYPORT CABLE

CONNECTORS

Connector A	Mini DisplayPort Male
Connector B	DisplayPort Male
Housing Material	Chromed plated ABS
Connector Plating	24K Gold 3µm
Pin Construction	Phosphor Bronze
Pin Plating	24K Gold 15µm
Dimensions (approx.) WxDxH	Mini DisplayPort: 10x32x7mm (0.39x1.26x0.28in) DisplayPort: 19.7x38.9x12mm (0.77x1.53x0.47in)

CABLE CONSTRUCTION

Length	5m [16.40ft]
Standard	DisplayPort 1.2
Colour	Grey
Type	Round
Jacket Diameter	6.5mm [0.256]
Jacket Material	PVC
Conductor Material	Tinned Copper
Conductor Gauge	30AWG
Shielding	Copper Braid 85%

SPECIFICATONS

Supported Bandwidth	21.6Gbps
Maximum Resolution	4096x2160@60Hz 4:4:4 10bit
Nominal Attenuation	300kHz-825MHz <5dB 825MHz-2.475GHz <5dB 2.475GHz-4.125GHz <12dB 4.125GHz-5.1GHz <20dB
Minimum Bend Radius	65mm [2.56in]
Operating Temperature	-20°C - 80°C [-4°F - 176°F]
Storage Temperature	-25°C - 85°C [-13°F - 185°F]
ATC Approved	-

MISCELLANEOUS

Packaging Type	Polybag
Warranty (Years)	10
Certificated	RoHS, REACH, UL

PURCHASING INFORMATION

No.	36314
EAN	4002888363143

AVAILABLE IN OTHER LENGTHS

36313 - 3m [9.84ft]
36314 - 5m [16.40ft]