

Part No **36482**

2M DISPLAYPORT 1.4 CABLE, ANTHRA LINE

DP MALE TO MALE



DESCRIPTION

Professional choice DisplayPort 1.4 cable for commercial and high performance AV and IT installations
Supports UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit including 4K 4096x2160@160Hz 4:4:4 8bit
Robust ABS housing 24K gold plated connectors and contacts
Triple shielded cable, corrosion resistant tinned copper 28AWG conductors
DisplayPort 1.4, 32.4Gbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Anthra Line DisplayPort cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line DisplayPort cables are premium connections that feature triple shielded with 28AWG tinned copper conductors for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 8K 7680x4320@60Hz 4:2:2 8bit, including 4K 4096x2160@160Hz 4:4:4 8bit and HDCP are supported.
DisplayPort 1.4 technology and DisplayPort compliance certification ensures compatibility with all DisplayPort enabled devices.

Anthra Line DisplayPort cables are available in lengths from 0.5m to 5m.

RELATED PRODUCTS

36480 - 0.5m [1.64ft]
36481 - 1m [3.28ft]
36482 - 2m [6.56ft]
36483 - 3m [9.84ft]
36484 - 5m [16.40ft]

2M DISPLAYPORT 1.4 CABLE, ANTHRA LINE

CONNECTORS

Connector A	DisplayPort Male
Connector B	DisplayPort Male
Housing Material	ABS
Connector Plating	24K Gold 15µm
Pin Construction	Phosphor Bronze
Pin Plating	24K Gold 3µm
Dimensions (approx.) WxDxH	21.0x38.9x13.6mm [0.83x1.53x0.54in]

SPECIFICATONS

Supported Bandwidth	32.4Gbit/s
Maximum Resolution	7680x4320@60Hz 4:2:2 8bit 4096x2160@120Hz 4:4:4 8bit
Nominal Attenuation	100MHz-450MHz <5.1dB, 450MHz-8100MHz <33.28dB
Minimum Bend Radius	58.4mm [2.14in]
Operating Temperature	-20°C - 80°C [-4°F - 176°F]
Storage Temperature	-25°C - 85°C [-13°F - 185°F]
ATC Approved	0

PURCHASING INFORMATION

No.	36482
EAN	4002888364829

CABLE CONSTRUCTION

Length	2m [6.56ft]
Standard	DisplayPort 1.4
Colour	Black
Type	Round
Jacket Diameter	7.3mm [0.29in]
Jacket Material	PVC
Conductor Material	Copper
Conductor Gauge	27AWG
Shielding	Copper Braid 65%

MISCELLANEOUS

Packaging Type	Polybag
Warranty (Years)	10
Certificated	RoHS, REACH, UL

AVAILABLE IN OTHER LENGTHS

36480 - 0.5m [1.64ft]
36481 - 1m [3.28ft]
36482 - 2m [6.56ft]
36483 - 3m [9.84ft]
36484 - 5m [16.40ft]