

Part No 36483

3M DISPLAYPORT 1.2 CABLE, ANTHRA LINE

DP MALE TO MALE



DESCRIPTION

Professional choice DisplayPort 1.2 cable for commercial and high performance AV and IT installations Supports UHD resolutions up to 4K 4096x2160@120Hz 4:2:2 8bit Robust ABS housing 24K gold plated connectors and contacts Triple shielded cable, corrosion resistant tinned copper 28AWG conductors

DisplayPort 1.2, 21.6Gbps; 10 year warranty

From the Lines cable connectivity concept developed by Lindy, Anthra Line DisplayPort cables are the professional choice for high performance connections in commercial AV and IT installations.

Anthra Line DisplayPort cables are premium connections that feature triple shielded with 28AWG tinned copper conductors for performance and corrosion resistance. High quality 24K gold plated contacts and connectors maintain optimal signal integrity and maximum reliability.

UHD resolutions up to 4K 4096x2160@120Hz 4:2:2 8bit and HDCP are supported. DisplayPort 1.2 technology and DisplayPort compliance certification ensures compatibility with all DisplayPort enabled devices.

Anthra Line DisplayPort cables are available in lengths from 0.5m to 5m.

RELATED PRODUCTS

36480 - 0.5m (1.64ft) 36481 - 1m (3.28ft) 36482 - 2m (6.56ft) 36483 - 3m (9.84ft) 36484 - 5m (16.40ft)

3M DISPLAYPORT 1.2 CABLE, ANTHRA LINE



CONNECTORS

Connector A Connector B Housing Material Connector Plating Pin Construction Pin Plating Dimensions (approx.) WxDxH

DisplayPort Male DisplayPort Male ABS 24K Gold 15µm Phosphor Bronze 24K Gold 3µm 21.0x38.9x13.6mm (0.83x1.53x0.54in)

CABLE CONSTRUCTION

Length Standard	3m (9.84ft) DisplayPort 1.2		
Colour	Black		
Туре	Round		
Jacket Diameter	7.3mm (0.29in)		
Jacket Material	PVC		
Conductor Material	Copper		
Conductor Gauge	27AWG		
Shielding	Copper Braid 65%		

SPECIFICATONS

Supported Bandwidth Maximum Resolution

21.6Gbps 4096x2160@60Hz 4:4:4 10bit

Nominal Attenuation

100MHz-450MHz <5.1dB, 450MHz-8100MHz <33.28dB

Minimum Bend Radius58.4Operating Temperature-20°Storage Temperature-25°ATC Approved0

58.4mm (2.14in) -20°C - 80°C (-4°F - 176°F) -25°C - 85°C (-13°F - 185°F) o

MISCELLANEOUS

Packaging Type Warranty (Years) Certificated Polybag 10 RoHS, REACH, UL

AVAILABLE IN OTHER LENGTHS

36480 - 0.5m (1.64ft) 36481 - 1m (3.28ft) 36482 - 2m (6.56ft) 36483 - 3m (9.84ft) 36484 - 5m (16.40ft)

PURCHASING INFORMATION

No. EAN 36483 4002888364836