

Part No. 38503

# 15M FIBRE OPTIC HYBRID USB TYPE C CABLE, AUDIO / VIDEO ONLY

CREATES A USB TYPE C VIDEO CONNECTION OVER LONG DISTANCES



## DESCRIPTION

- Combines copper and fibre optic cable for a hybrid, long distance USB Type C connectivity solution
- Supplied as a Type C Male to Male cable for Video data only
- Supports resolutions up to 4K UHD 3840x2160@60Hz with additional support for HDR
- No external power required
- 2 year warranty

Lindy's Fibre Optic Hybrid USB Type C Cables are the professional solution for the transmission of USB video signals over longer distances. Combining the long-distance capabilities, flexibility and high EMI & RFI resistance of fibre optic cable with standard copper cabling, these hybrid cables are ideal for use in mission-critical AV setups or commercial installations. Supplied as a thin cable with a premium metal, narrow USB Type C connector, this cable can easily be installed through conduits and other narrow spaces with no damage caused to the internal cable structure.

Supporting all the features that come with the DP 1.2 specification, these cables deliver resolutions up to 4K UHD 3840x2160@60Hz, perfect for ensuring superior image quality in eye-catching retail displays, immersive AV installations at events or a responsive, crystal-clear solution in transportation signage. HDR support ensures a much wider colour gamut, greater contrasts and an enhanced brightness to provide eye-catching content even in outdoor or brightly lit scenarios.

## RELATED PRODUCTS

0

# 15M FIBRE OPTIC HYBRID USB TYPE C CABLE, AUDIO / VIDEO ONLY



## CONNECTORS

<b>Connector A</b>	USB Type C Male
<b>Connector B</b>	USB Type C Male
<b>Housing Material</b>	Zinc Alloy
<b>Connector Plating</b>	Gold Plated
<b>Pin Construction</b>	Brass
<b>Pin Plating</b>	Gold Plated
<b>Dimensions (approx.) WxDxH</b>	39mmx15mmx7.5mm [1.55 in x0.59in x0.3in]

## CABLE CONSTRUCTION

Length	15m [49.21ft]
Standard	DisplayPort 1.2
Colour	Black
Type	Round
Jacket Diameter	4.5mm [0.177in]
Jacket Material	PVC
Conductor Material	Tinned Copper

## SPECIFICATONS

Supported Bandwidth	21.6Gbps
Maximum Resolution	3840x2160@60Hz 4:4:4 10bit, 3840x2160@60Hz RGB 8bit
Nominal Attenuation	-1dB~-2dB
Minimum Bend Radius	45mm [1.77in]
Operating Temperature	0°C - 50°C [32°F - 122°F]
Storage Temperature	-25°C - 85°C [-13°F - 185°F]

## MISCELLANEOUS

Packaging Type	Carton box
Warranty (Years)	2
Certificated	CE, FCC, RoHS, REACH & California Proposition 65

## PURCHASING INFORMATION

No.	38503
EAN	4002888385039

## AVAILABLE IN OTHER LENGTHS

38501 - 5m [16.40ft]
38503 - 15m [49.21ft]
38505 - 30m [98.42ft]