

Part No **41718** 

# **DISPLAYPORT 1.2 TO HDMI CONVERTER**

CONNECTS A DISPLAYPORT SOURCE TO AN HDMI MONITOR



#### DESCRIPTION

- Converts a DisplayPort signal into HDMI
- Supports resolutions up to 4K 3840x2160@30Hz
- · Audio pass-through if supported by the video source
- Quick and simple Plug & Play installation
- 2 year warranty

The Lindy DisplayPort 1.2 to HDMI Converter is ideal for connecting a DisplayPort equipped source such as a PC or laptop to an HDMI monitor or TV. It supports resolutions up to 4K 3840x2160@30Hz and allows audio pass-through if supported by the video source.

The converter can also be used to add another display to extend the available desktop workspace and increase productivity. It is also ideally suited for travelling due to its compact, lightweight form factor and convenient Plug & Play installation.

RELATED PRODUCTS

N/A

### **DISPLAYPORT 1.2 TO HDMI CONVERTER**



#### SPECIFICATIONS

AV Interface	DisplayPort to HDMI	Input	DisplayPort Male
Interface Standard	DisplayPort 1.2, HDMI 1.4		
Supported Bandwidth	21.6Gbps		
Maximum Input Resolution	3840x2160@30Hz		
		Output	HDMI Type A Female
Maximum Output Resolution	3840x2160@30Hz		
		MISCELLANEOUS	
Chipset	PS8402A	Packaging Type	Polybag
		Packaging Dimension	160x160x20mm (6.3x6.3x0.79in)
		Gross Weight	0.038kg (0.08lb)
HDCP Support	HDCP 1.4	Warranty (Years)	2
Supported Audio	Pass-through	Certificated	CE, FCC, RoHS, REACH
Separate Audio Ports	-		

CONNECTORS

### **PHYSICAL PROPERTIES**

Dimensions (approx.) WxDxH

20.8x51x11.5mm (0.82x2.01x0.45in) / HDMI 20.1x44.5x9mm (0.79x1.75x0.35in)

Cable Length

150mm (5.91in)

## EAN 4002888417181

No.

**PURCHASING INFORMATION** 

41718

**PACKAGING CONTENTS** 

DisplayPort 1.2 to HDMI 1.4 Converter

ABS	
PVC	
5mm (0.2in)	
60mm (2.36in)	
0.03kg (0.07lb)	
0°C - 80°C (32°F - 176°F)	
-20°C - 70°C (-4°F - 158°F)	
10 - 85% RH (non-condensing)	
Black	