

Part No. **43098**

10M USB 3.0 ACTIVE CABLE

10M USB 3.0 EXTENSION FOR DIRECT DEVICE CONNECTION



DESCRIPTION

• 10 metre USB 3.0 Active Repeater Cable

Supports transfer rates up to 5Gbps

Ideal for direct device connection

Plug & Play installation

• 2 year warranty

The Lindy USB 3.0 Active Cable uses built-in active electronics to extend the cable length of a USB 3.0 device by an additional 10m whilst continuing to support data transfer rates of up to 5Gbps. With USB A male and USB B male connectors this product allows Type B devices such as printers to be connected directly at longer distances and ensures flexible positioning.

The Lindy USB 3.0 Active Extension Cable is compatible with all USB Type A equipped computers. With plug and play functionality, this extension cable can be installed quickly and with minimum fuss.

It is recommended that this extender is used with low power or self powered USB peripherals and not high power consuming devices, unless they have their own power supply.

RELATED PRODUCTS

0

10M USB 3.0 ACTIVE CABLE



CONNECTORS

| Connector A |
|----------------------------|
| Connector B |
| Power |
| Housing Material |
| Connector Plating |
| Pin Construction |
| Pin Plating |
| Dimensions (approx.) WxDxH |
| |

USB Type A Male USB Type B Male -Plastic Nickel Copper Nickel USB A Male: 16x49x9mm (0.63x3.7x0.35in) USB B Male: 10x52x13mm (0.39x2.05x0.51in) Repeater (2x): 35x100x15mm

CABLE CONSTRUCTION

| Length | 10m (32.8ft) |
|---------------------------|------------------------------------|
| Standard | USB 3.1 Gen 1 / 3.0 |
| Colour | Black |
| Туре | Round |
| Jacket Diameter | 7mm +/- 0.15mm (0.28in +/- 0.01in) |
| Jacket Material | PVC |
| Conductor Material | Copper |
| Conductor Gauge | 28/28/22AWG |
| Shielding | 85% Aluminium |

SPECIFICATONS

Supported Bandwidth Nominal Attenuation 5 Gbps 100 MHz, -1.5 dB 1.25 GHz, -5.0 dB 2.5 GHz, -7.5 dB 7.5 GHz, -25 dB

MISCELLANEOUS

| Packaging Type | Polybag |
|----------------------|--------------------------------------|
| Packaging Dimensions | 300x300x80mm (11.81x11.81x3.15in) |
| Net Weight | 0.5kg (1.1lb) |
| Gross Weight | 0.530kg (1.17lb) |
| Warranty (Years) | 2 |
| Certificated | CE, FCC, RoHS & REACH |

AVAILABLE IN OTHER LENGTHS

0

Minimum Bend Radius Maximum Tensile Load Operating Temperature Storage Temperature Transmission Medium Transmission Technology

60mm (2.36in) N/A 0°C - 55°C (32°F - 131°F) -20°C - 85°C (-4°F - 185°F) Twisted Pair USB 3.0

PURCHASING INFORMATION

No. EAN 43098 4002888430982

THIS PRODUCT IS ALSO AVAILABLE IN OTHER LENGTHS

0