

Part No 43156

10M USB 3.0 ACTIVE EXTENSION

10M USB 3.0 EXTENSION OF A USB TYPE A PORT OF YOUR COMPUTER



DESCRIPTION RELATED PRODUCTS

- \cdot 10 metre USB 3.0 Active Extension Repeater Lead
- Supports transfer rates up to 5Gbps
- For even greater distances simply connect 2 cables in series
- Plug & Play
- 2 year warranty

The Lindy USB 3.0 Active Extension Cable uses built-in active electronics to extend the cable length of a USB 3.0 device by an additional 10m whilst continuing to support data transfer rates of up to 5Gbps. With its USB A male and USB A female connector it allows Type A devices such as storage devices, webcams and other Type A devices to be connected at longer distances to PCs, laptops and tablets, while also ensuring flexible positioning. Up to 2 extension cables can be chained together to achieve a distance of 20m.

The Lindy USB 3.0 Active Extension Cable is compatible with all USB Type A equipped computers. With plug and play functionality, this extension cable can be installed quickly and with minimum fuss, ideal for both professional and first time users. The USB active extension cable also features a DC socket for connecting an external power supply (not included) when using USB peripherals which have higher power requirements.

N/A

10M USB 3.0 ACTIVE EXTENSION



CONNECTORS

Connector A USB Type A Male
Connector B USB Type A Female

Power 3.5/1.35mm DC Connector

Housing Material Plastic
Connector Plating Nickel
Pin Construction Copper
Pin Plating Golden

Dimensions (approx.) WxDxH USB A Male: 16x37x9.8mm

(0.63x1.46x0.39in)

USB A Female: 32x85x10mm

(1.26x3.35x0.39in)

CABLE CONSTRUCTION

Length 10m (32.81ft)

Standard USB 3.1 Gen 1 / 3.0

Colour Black
Type Round

Jacket Diameter 6mm (0.24in)

Jacket Material PVC

Conductor Material Tinned Copper Conductor Gauge 28/28/22AWG

Shielding 85% Aluminium magnesium braid

SPECIFICATONS

Supported Bandwidth 5 Gbps

Nominal Attenuation (100 MHz, -1.5 dB),

(1.25 GHz, -5.0 dB), (2.5 GHz, -7.5 dB), (7.5 GHz, -25 dB) **MISCELLANEOUS**

Packaging Type Carton Box

Packaging Dimensions 150x140x90mm (5.91x5.51x3.54in)

Net Weight 0.515kg (1.14lb) Gross Weight 0.6kg (1.32lb)

Warranty (Years) 2

Certificated CE, FCC, RoHS & REACH

AVAILABLE IN OTHER LENGTHS

Minimum Bend Radius 60mm (2.36in)

Maximum Tensile Load

Operating Temperature $0^{\circ}\text{C} - 55^{\circ}\text{C} (32^{\circ}\text{F} - 131^{\circ}\text{F})$ Storage Temperature $-20^{\circ}\text{C} - 70^{\circ}\text{C} (-4^{\circ}\text{F} - 185^{\circ}\text{F})$

Transmission Medium Twisted Pair
Transmission Technology USB 3.1 Gen 1 / 3.0

43156 - 10m (32.81ft)

PURCHASING INFORMATION

No. 43156

EAN 4002888431569

THIS PRODUCT IS ALSO AVAILABLE IN OTHER LENGTHS

43156 - 10m (32.81ft)