



Datenblatt - Fiche technique - Data sheet




**11.99.5522**



VALUE Kabel DVI (18+1) ST - HDMI ST, 2,0m

VALUE Câble de raccordement pour écran DVI (18+1) M /HDMI M, 2,0m

VALUE Monitor Cable, DVI (18+1) - HDMI, M/M, 2 m



P/N	L(mm)
11.99.5519	1000±30mm
11.99.5522	2000±50mm
11.99.5532	3000±70mm
11.99.5552	5000±70mm

NOTES:

1. MATERIAL

- 1.1 HDMI CABLE: (7/0.10TC\*1P+7/0.10TC+FAM)\*4PCS+7/0.12TC\*3C+7/0.12TC\*1P+AL+7/0.12TC+128/0.12ALM+BLACK PVC JACKET.  
OD:  $\varnothing 6.0 \pm 0.2$  mm
- 1.2 HDMI 19PIN TYPE A MALE : BLACK INSULATION, GOLD PLATED CONTACTS, NICKEL PLATED SHELL.
- 1.3 DVI(18+1) MALE: BLACK INSULATION, GOLD PLATED CONTACTS G/F, NICKEL PLATED SHELL.
- 1.4 THUMB SCREW TO BE MOLDED BLACK PVC. NICKEL PLATED SCREW.
- 1.5 ALL HOOD: MOLDED BLACK PVC.

2. ELECTRICAL

- 2.1 100% OPEN AND SHORT TEST.
- 2.2 CONDUCTOR RESISTANCE: 5 OHMS MAX.
- 2.3 INSULATION RESISTANCE: 10 MEGOHMS MIN.
- 2.4 HI-POT: DC300V/0.01S.

3. PACKAGING: A PC/PE-BAG PACKAGING .

4. ALL MATERIALS ARE REACH COMPLIANT.

LENGTH TOLERANCE: X. $\pm 0.5$ .X $\pm 0.2$ .XX $\pm 0.1$	SCALE: FREE	
ANGLE TOLERANCE: X' $\pm 3'$ .X' $\pm 1'$	UNIT: mm	
	VERSION: 02	PAGE: 1/1

<b>Rotronic Co., Ltd.</b>		ENG:
VALUE DVI Cable, DVI M-HDMI M, black		CHECKED:
		APPROVED:

REV.	MODIFY DESCRIPTION	DATE
02	ADD THE ONE	2012-01-05
01	CHANGE THE CABLE MARKING	2011-02-23
00	NEW ISSUE	2010-03-16