




Datenblatt - Fiche technique - Data sheet

21.15.0921






ROLINE UTP-Patchkabel Kat.6, orange, 1,5 m

Cordon ROLINE Cat.6 UTP, orange, 1,5 m

ROLINE UTP Patch Cord, Cat.6, orange, 1.5 m

Total length (optional)



Remark : SCABAXX013X XXX XE1201

(1) XX : Jacket Color

01=Black(RAL9011), 02=Gray(RAL7035), 03=Red(RAL3031)
05=White(RAL9010), 06=Yellow(RAL1021), 07=Blue(RAL5015)
08=Green(RAL6029), 09=Orange(RAL2003), 10=Purple(RAL4005)
11=Pink(RAL4003)

(2) X : Wiring

1=T568A, 2=T568B, 3=T568A & T568B combination

(3) XXX : Length

(4) Length Unit : 1=cm, 2=meter, 3=feet.

(3)(4) : 0501=0.5meter(50cm), 0012=1meter, 0102=10meter
0033=3feet, 0103=10feet

Specification :

Material :

- RJ45 Plug : (P/N : PU8850)
 - Housing : Polycarbonate, UL 94V-2, Transparent color.
 - Contact material : Phosphor Bronze with 50-60 micro-inch Nickel plated.
 - Contact finished : Min. 50 micro-inch Gold plated.
- Narrow PVC Molded.
- Cable : UTP UnShielded and Twisted,
 - 4 pair Stranded wire UL material approved.
 - 24 AWG conductor and PVC jacket.
- length mark(latch side) : 0.3M,0.5M,0.75M,1M,1.5M,2M,3M,5M,7M,7.5M,10M,15M,20M,25M,30M.
- Print : roline UTP PATCH CABLE 24AWG 4PR EIA/TIA-568B.2-1
CAT.6 XXXXXX-X

GENERAL
TOLERANCE
OR
DIMENSIONS
X.XXX ±0.005
X.XX ±0.05
X.X ±0.1

DRAWING 17.MAR.2009 Connie
CHECK 17.MAR.2009 KLi
APPROVAL 17.MAR.2009 Yty

SCALE 1/1 (A4) UNIT mm
DRAWING NO. 21.15.XXXX(SA1)
DRAWING CLASSIFICATION

NAME
ITEM NO.: 21.15.XXXX
DES.: C6 UTP Patch Cord

SHEET 1 OF 1
A1

rotronic