



Datenblatt - Fiche technique - Data sheet

21.15.1344




ROLINE S/FTP-(PiMF-)Patchkabel Kat.6, blau, 2m


Cordon ROLINE Cat.6 S/FTP (PiMF) bleu, 2,0m

ROLINE S/FTP (PiMF) Patch Cord, Cat.6, blue, 2.0m


Total length (optional)



A



Print: roline SSTP PATCH CABLE 26AWG 4PR ISO/IEC11801 & EN50288 CAT.6
XXXXXXXX-X



B

Remark : SCAEAXX017X XXX X E1201
(1) (2) (3) (4)

Remack#

21.15.0823	1.5m	grey	21.15.1346	2.0m	white
21.15.0824	1.5m	red	21.15.1356	3.0m	white
21.15.0825	1.5m	yellow	21.15.1366	5.0m	white
21.15.0826	1.5m	green	21.15.1376	7.0m	white
21.15.0827	1.5m	blue	21.15.1386	10m	white
21.15.0828	1.5m	black	21.15.1396	15m	white
21.15.0829	1.5m	white	21.15.1406	20m	white
21.15.1316	0.3m	white			
21.15.1326	0.5m	white			
21.15.1336	1.0m	white			

Specification :

Material :

1. RJ45 Plug : (JE P/N : P028850)
- 1-1. Housing : Polycarbonate, UL 94V-2, Transparent color.
- 1-2. Contact material : Phosphor Bronze with 50-60 micro-inch Nickel plated.
- 1-3. Contact finished : Min. 50 micro-inch Gold plated on surface contact area.
- 1-4. Shield : Bronze with Nickel plated.
2. Molding : PVC.
3. Cable :
 - 3-1. Jacket : PVC.
 - 3-2. Conductor : 26 AWG stranded copper.
 - 3-3. Isolation : PE.
 - 3-4. Shield : Aluminum Foil Shielded for Each Pair, Tin Copper Braid.
4. Cable structure : S/FTP, 4 twisted pair.

C

Rotronic Co.,LTd.

GENERAL TOLERANCE OF DIMENSIONS X.XXX ±0.005 X.XX ±0.05 X.X ±0.1	DRAWING	10.JAN.2011	Abby
	CHECK	10.JAN.2011	Maer
	APPROVAL	10.JAN.2011	YTY
	SCALE	1/1 (A4)	UNIT mm
		DATE	NAME
		DRAWING NO.	ITEM NO.:SCAEAXX017XXXXXE1201
		DRAWING CLASSIFICATION	DES.: C6 S/FTP Patch Cord
		DRAWING NO.	SCAEAXX017XXXXXE1201(SA1)
		SHEET	1 OF 1

		10cm	5	6
		4	3	2
		0	1	0