

1

2

3

4

5

6

length±xxmm

PLUG A

PIN.8

PIN.1

PLUG B

PIN.1

PIN.8

6.6±0.1

21.2±0.3

24.0±0.3

12.0±0.1

length mark

roline S/FTP PATCH CABLE 26AWG 4PR ISO/IEC 11801 & EN50288 CAT.6A LSOH XXXXXX-X

11.7±0.1

Specification :

Material :

- 1. RJ45 Plug : (JE P/N : PUY8850)
 - 1-1. Housing : Polycarbonate, UL 94V-2, Transparent color
 - 1-2. Contact material : Phosphor Bronze with 50-60 micro-inch Nickel plated
 - 1-3. Contact finished : Min. 50 micro-inch Gold plated on surface contact area
 - 1-4. Shield : Bronze with Nickel plated
- 2. SR : SR-V95 FOR S/FTP Boot with nose
- 3. Cable :
 - 3-1. Jacket : LSOH
 - 3-2. Conductor : 26 AWG stranded copper
 - 3-3. Isolation : PE
 - 3-4. Shield : Aluminum Foil Shielded for Each Pair, copper clad with steel braid
- 4. Cable structure : S/FTP, 4 twisted pair
- 5. Minimum Banding Radius: 50mm

- (1)Jacket Color:Black(RAL9011)
- (2)Wiring:T568B

item no.	length	tolerance
21.15.1960	0.5M	+20 -0
21.15.1961	1M	+20 -0
21.15.1962	2M	+20 -10
21.15.1963	3M	+20 -10
21.15.1965	5M	+30 -20
21.15.1966	7M	+30 -20
21.15.1967	10M	+30 -20
21.15.1968	15M	+30 -20
21.15.1969	20M	+70 -30

item no	21.15.1960	21.15.1961	21.15.1962	21.15.1963	21.15.1965
	21.15.1966	21.15.1967	21.15.1968	21.15.1969	

Desc ROLINE Cat 6a S/FTP Patch Cord,LSOH.Component Level,black

"#": Matching DIM.	DRAWING	25.Aug.2015	byz
"*": Important DIM.	CHECK	25.Aug.2015	Jane
Others General DIM.	APPROVAL	25.Aug.2015	Jaimy
GENERAL TOLERANCE OF DIMENSIONS	DATE		NAME
X.XXX ±0.005	SCALE	1/1(A4)	UNIT mm
X.XX ±0.05			
X.X ±0.1			

SECOMP

No.	MODIFIED AREA	ORIGINAL	MODIFY	DATE	MODIFIER
-----	---------------	----------	--------	------	----------

DRAWING NO.	
DRAWING CLASSIFICATION	S SHEET 1 OF 1

1

2

0

3

4

10cm

5

6

A1