



$L \pm xx \text{ mm}$



WIRING DIAGRAM(568B)



NOTE:

1. ELECTRICAL TEST:

- (1). 100% OPEN SHORT, MISS WIRE TEST
- (2). INSULATION RESISTANCE:DC 300V 10MΩ ;
- (3). CONDUCTOR RESISTANCE:3Ω Max (More than 3m, add one ohm per meter) ;

2. Fluke channel link test:

TEST LIMIT:ISO11801 Channel Class Ea

3. PRINT WORD:

CAT.6A S/FTP LSZH 500MHz ISO/IEC 11801 & EN 50173-1 & ANSI/TIA-568-C.2

4. ROHS2.0 & REACH COMPLIANT

5. Minimum of the bending radius is 50mm

(Suitable for all meters)

MATERIAL LIST

③	OVER MOLD	PVC 75A SEE THE CHART	2	
②	CONNECTOR	RJ45 8P8C Shielded Plug, Pin Gold Plated 3u", Shell Nickel Plating, Transparence blue	2	
①	CABLE	S/FTP CAT.6A 27AWG(7/0.135Bare Copper*1P+AL-FOIL)*4PAIRS+BRAID (5*16/0.12mmAL-MG) COLOUR:RED/199C JACKET:LSZH OD:6.2±0.2mm	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK
		NEW	2015-10-21	A
BY	CHK	REVISION RECORD MODIFICATION	DATE	REV.

COLOUR: RED (PANTONE 199C)		
ITEM NO.	LENGTH	TOLERANCE
21.99.1920	0.5m	±15mm
21.99.1921	1m	±30mm
21.99.1922	2m	±60mm
21.99.1923	3m	±90mm
21.99.1925	5m	±150mm
21.99.1926	7m	±210mm
21.99.1927	10m	±300mm
21.99.1928	15m	±450mm
21.99.1929	20m	±600mm

ITEM NO.	21.99.1920	21.99.1921	21.99.1922	21.99.1923	21.99.1925
	21.99.1926	21.99.1927	21.99.1928	21.99.1929	
DESC.	VALUE S/FTP CAT.6a Patch Cord, red				

